



BOYSEN® PERMA-PUTTY™

High-Build Masonry Putty



For technical reasons connected with color reproduction and paint manufacturing, the colors shown may not match the exact paint color.

BOYSEN® PERMA-PUTTY™ B-7312

High-Build Masonry Putty

BOYSEN® Perma-Putty™ is a water-based, high-build, lightweight masonry putty specifically developed for correcting minor surface imperfections up to 2mm. It exhibits both excellent sandability and fast-drying properties, making it an excellent choice for any project. It is ideal for interior concrete, stucco, and plaster substrates.

APPLICATION SCHEDULE

Primer: BOYSEN® Permacoat™ Flat Latex B-701

Putty: BOYSEN® Perma-Putty™ B-7312 (for interior use only)

Spot Primer: BOYSEN® Permacoat™ Flat Latex B-701

Topcoat: BOYSEN® Permacoat™ Latex and other water-based products (e.g., Virtuoso™ Silk Touch™, BOYSEN® Healthy Home™, etc.)



PRACTICAL COVERAGE PER 4-LITERS

2mm thickness: 4-5 sq. m.

*Depending on surface texture and porosity



PACKAGING

Available in 4-Liters



APPLICATION

By putty knife



DRYING TIME

Touch dry in 30 minutes.
Recoat/Sanding in 2 hours.

PACIFIC PAINT (BOYSEN) PHILIPPINES, INC.

MAIN OFFICE:

292 D. Tuazon Street, 1115 Quezon City
Hotline: 8364-9999
Tel Nos. 8364-3505 to 09; 8365-0561 to 64
Fax Numbers: 8367-8881; 8361-7164
inquiry@boysen.com.ph
www.boysen.com.ph

MARKETING AND TECHNICAL OFFICE:

276-278 D. Tuazon Street, 1115 Quezon City
Tel. Nos. 8363-9738; 8367-8880
Fax No. 8367-8878
Mobile Nos. 0918-913-6000
marketing@boysen.com.ph
technical@boysen.com.ph

BOYSEN®



The No. 1 PAINT

For technical reasons connected with color reproduction and paint manufacturing, the colors shown may not match the exact paint color.