

For technical reasons connected with color reproduction and paint manufacturing, the colors shown may not match the exact paint color

BOYSEN® PRIMEGUARD™

A water-based acrylic primer designed to have excellent adhesion to metal substrates such as stainless steel, aluminum, and galvanized surfaces.

FEATURES:

- EXCEPTIONAL ADHESION It has exceptional adhesion on galvanized iron, stainless steel, and aluminum substrates. It is also compatible with most topcoats.
- ENVIRONMENTALLY SOUND It is relatively low in odor, non-flammable, and does not contain hazardous solvents or lead

RAPID DRYING

It touch dries in 2 hours compared to 12 hours for its enamel-based counterpart. This results in faster paint jobs and significant labor cost savings.

EASY WATER CLEAN-UP No need for thinners and solvent reducers. Painting tools and spills can be easily

cleaned with soap and water.



For technical reasons connected with color reproduction and paint manufacturing, the colors shown may not match the exact paint color

SURFACE PREPARATION

Wipe the surface with a rag soaked in paint thinner to remove grease, oil, wax and other foreign matter.

For recoating pre-painted galvanized surfaces in good condition, wipe the surface with a clean rag before applying paint. Remove all loose paint film to sound surface. Spot prime bare substrate.

PAINTING SCHEDULE

NEW METAL

Primer: BOYSEN® Primeguard™

2nd & 3rd coat:

BOYSEN® Roofgard™, BOYSEN® Acqua Epoxy™ BOYSEN® Epoxy Enamel, BOYSEN® Acrytex™

BOYSEN® Quick Drying Enamel, BOYSEN® Cool Shades™

TECHNICAL DATA

VEHICLE TYPE:

Acrvlic

DRY TIME:

Touch: 1 hour Recoat: 2 hours

*Measured at 25° C and 50% relative

humidity

PRACTICAL COVERAGE per 4-LITERS:

25-30 sq. m.

*Depending on surface texture and

porosity

TINTING:

Not Applicable

THINNING SOLVENT:

Use as supplied

CLEAN-UP SOLVENT:

Water


PACKAGING:

4-Liters

APPLICATION:

By brush, roller or airless spray

AVAILABLE COLORS



B-4301 White

Red Oxide

B-4320 Gray

*Due to technical reasons connected with ink-printing and color reproduction, swatches shown here may differ from the exact paint color. Always refer to actual paint color standards to confirm your color.



PACIFIC PAINT (BOYSEN) PHILIPPINES, INC.

292 D. Tuazon Street, 1115 Quezon City, Philippines

Hotline: 8364-9999
Tel. Nos. 8364-3505 to 09; 8365-0561 to 64
Fax Nos. 8367-8881; 8361-7164
inquiry@boysen.com.ph
www.boysen.com.ph



SP 241-242 2nd Level, IKEA Retail Integration
South Parking Building, SM Mall of Asia, Pasay City 1300



Boysen®, Boysen® Eagle symbol and Primeguard™ are registered trademarks of Pacific Paint (BOYSEN) Philippines, Inc.